



PHYSICAL

(2) SHIELDED PARALLEL PAIRS

30 AWG SOLID SILVER PLATED COPPER

.047 NOM DIAMETER FOAM POLYOLEFIN, WHITE

PARALLEL PAIR

.001 ALUMINIZED POLYESTER, SPIRAL, FOIL OUT, 20% MIN OVERLAP,
HEAT SEALED, "1" PRINTED ON ONE PAIR, "2" PRINTED ON OTHER

CABLING: TWISTED TO ROUND

OVERALL SHIELD {1}: .002 ALUM-POLYESTER-ALUM, SPIRAL, 20% MIN OVERLAP

OVERALL SHIELD {2}: 36 AWG TINNED COPPER BRAID, 85% MIN COVERAGE

JACKET: .025 NOM WALL PVC, BLACK

DIAMETER: .205 ± .015

PRINT LEGEND: AMPHENOL SPECTRA-STRIP SKEWCLEAR® 30 AWG FIBRE CHANNEL 2X
2 PAIR (UL) 75° C CL2 CSA AWM I/II A 75° C 300V FT4

ELECTRICAL

IMPEDANCE: 150 ± 7 Ω (DIFFERENTIAL TDR)

CAPACITANCE: 28 pF / M NOMINAL

PROP DELAY: 4.25 ns / M NOMINAL

SKREW (WITHIN PAIR): ≤ 125 ps / 10 M (REF ≤ 12.5 ps / M)

(TDT METHOD PER QAP 6-14, PAIR SHIELD GROUNDED)

(DIFFERENTIAL 50%-50%, TEKTRONIX 11801, SD-24/SD-26 SAMPLING HEADS)

CROSSTALK: BETTER THAN -45 dB @ 1 GHz (0.6 % VOLTAGE, REF)

ATTENUATION (NOMINAL): 0.60 dB / M @ 531.25 MHz (1.0625 Gb)

USING 150 Ω ADAPTERS 0.86 dB / M @ 1062.5 MHz (2.125 Gb)

0.94 dB / M @ 1250 MHz (2.500 Gb)

1.05 dB / M @ 1562.5 MHz (3.125 Gb)

APPROVALS

UL / CSA: UL CL2 CSA FT4 75° C

ALL DIMENSIONS ARE INCHES UNLESS OTHERWISE NOTED

| REVISION | CHANGES |
|----------|------------------|
| A | RELEASE |
| B | SKEW TEST METHOD |
| C | IMPEDANCE, SKEW |
| D | PRINT LEGEND |

| | | | | | | | |
|-----------------------------|----------|----|-----|---------|--|---|------------|
| DRAWN BY GPV 12-16-98 | PROD ENG | QA | MKT | P/ECN # | DRAWING NO. 160-3099-998 | AMPHENOL SPECTRA-STRIP OPERATIONS 720 Sherman Ave Tel (203) 281-3200 Hamden CT. 06514 Fax (203) 281-5872 | Rev D |
| | | | | | TITLE: (2) SHIELDED PAIRS, 150 OHM, 30 AWG | | Sheet |
| | | | | | | | SKEWCLEAR® |